

TA134



TA200



TA201



TA202



Tip:	TA134	TA200	TA201	TA202
Glavne značilnosti:	dve mejni vrednosti	1 frekvenčni vhod	2 frekvenčna vhoda	2 frekvenčna vhoda, 2 mejni vrednosti
Napetost:	24, 48, 115, 230 VAC, 12...30 VDC	24, 48, 115, 230 VAC, 24 VDC	24, 48, 115, 230 VAC, 24 VDC	24, 48, 115, 230 VAC, 24 VDC
Poraba:	5 VA, 4 W	6 VA, 4 W	6 VA, 4 W	7 VA, 5 W
Napetost senzorjev 12...26 VDC:	maks. 60 mA	maks. 100 mA	maks. 100 mA	maks. 100 mA
Vhodi:	A, B, 3 kontr.vhodi	F1	F1, F2/Start, Stop	F1, F2/Start, Stop
Vhodna frekvenca:	25 Hz, 40 kHz	25 Hz, 40 kHz	25 Hz, 10 / 40 kHz	25 Hz, 10 / 40 kHz
Izhodi:	elektr. ali rele	–	–	elektr. in rele
Vmesnik:	RS485	–	–	RS232 / 422 / 485
Prikaz:	LCD, 6-mestni	LED, 6-mestni	LED, 6-mestni	LED, 6-mestni
Čelne dimenzije:	48 x 48 mm	96 x 48 mm	96 x 48 mm	96 x 48 mm
Posebnosti:	dodatna osvetlitev	–	funkcija računanja	funkcija računanja in mejne vrednosti